

Electrical & Fans



Indoor/Outdoor Extension Cords

Our 12/3 Outdoor Extension Cords are tailored specifically for the event rental industry and feature a high visibility P.V.C. jacket that withstands rough use, chemicals, moisture, and ozone and provides added flexibility at below freezing temperatures. The molded-on non-slip plugs, available in single tap and triple tap, resist breaking or pulling off. Our white cords are best suited for applications with light backdrops such as white tent tops, sidewalls and white pole covers. For dark backdrops, such as pavement or grass, our 25' black single tap cord is ideal. The 10' molded on triple tap cord is a perfect power source for lighting clusters affixed to center poles. All of our extension cords are U.L. Listed and meet OSHA requirements. See the table below for a complete listing of our single and triple tap extension cord selection.

Description	Product Code
25' White 12/3 Single Tap	D14512025
50' White 12/3 Single Tap	D14512050
100' White 12/3 Single Tap	D14512100
10' White 12/3 W/Trip Tap	D15613010
25' Black 12/3 Single Tap	D16624025

Triple Tap Adapters

Features:

- Convert any of our 12/3 Extension Cords into a 3-Outlet Cord
- Abrasion resistant P.V.C. Molded Shell
- 15A-125V
- U.L. Listed

Description	Product Code
Triple Tap Adapter	D101/COLOR



Available in Black or White



**Durable Pro Cap™
Outlet Covers Keep
Dirt and Moisture Out.**

50' White Multi Outlet Cord

Our 50' White 12/3 Multi Outlet Extension Cord features six outlets with Pro Cap™ covers to keep dirt and moisture out of unused sockets.

Features:

- 15A-125V
- 50', Six Outlets
- -40F Cold weather Jacket
- U.L. Listed

Description	Product Code
50' White 12/3 Multi Outlet Ext. Cord	D12420050

GFCI In-line Shock Protector™

With Lighted Triple Tap End!

Features:

- Triple tap features Primelight™ power indicator light
- 3ft. 12/3 SJTW power cord has in-line GFCI for shock protection
- Rated for up to 15 Amps or 1,875 Watts
- Ultra flexible up to -40 Degrees F.
- U.L. Listed and meets all OSHA requirements



Description	Product Code
3' Inline GFCI	GF320803

GFCI Surge Protectors are recommended for all outdoor lighting/electrical installations

DURADIMMER™ 1,000W

Features:

- Maximum 1,000 Watt Capacity
- Includes: 1 - Premium Lutron Slide Dimmer & 1 - 15A, 120V G.F.C.I. Receptacle (two outlets)
- Constructed of extremely durable Die Cast Aluminum
- Satisfies code for water tightness when outlet cover is closed
- Powered by a 18/3, 5' 8" power cord with molded on grounded plug (white and black cords available)
- Assembled in USA of U.L. Listed Components



Convenient Slide Style Dimmer makes operation Easy!

Description	Product Code
DuraDimmer - 1,000W	DD1000W

18" Mountable Tent Fan

Features:

- Low Profile white housing makes it ideal for use in tents
- Quiet operation
- UL507 certified motor for indoor and outdoor use
- Corrosion resistant, powder coated fan guards meet OSHA 1910.212(a)(5) requirements
- Powder coated guards and bracket for corrosion resistance

Specifications:

- Motor: 1/8 HP, 115 Volts, 3 Speed
- CFM: 3,120, 2,650, 2,010
- Cord: 8' Three prong pre-wired plug
- Amp Draw: Up to 1.4 amps
- Fan guard diameter: 21"
- Fan guard depth: 6.5"
- Weight: 20 lbs. excluding the clamp



**UL 507
Certified for Indoor/
Outdoor Use!**



The Pole Mount Bracket (shown right) enables you to easily mount the fan in horizontal or vertical orientations. Fits the following: 2"-2.375" Round Pipe, 1.5" X 2.5" Wood Tent Poles, 2.5" X 2.5" ATF Brand Octagonal Wood Tent Poles.

Description	Product Code
18" Fan, White, UL	18MFULW
Pole Mount Bracket, White	FPMBW